

→ color (G)

Product Data-Sheet

No. 9403 - R - 05

Edition: Oct 2009

1. Application Sector

DAMTEC® color G is grinded on one side and with its special selection of raw materials excellent below linoleum and PVC flooring. Since its plasticizer-free formulation and its grinded surface eliminates the need for a separating layer to prevent unsightly migration and softener discoloration in floor finish.

With its mixture from natural raw materials - rubber and cork - **DAMTEC® color G** is an excellent insulating underlay for floors in residential and other buildings.

DAMTEC® color without grinded surface is also suitable under parquet and laminate floor as well as under textile floors.

2. Material

High-quality granules of recycled rubber and cork with PU elastomer bonding agent

3. Appearance

colour:	multicoloured
surface:	granular texture

4. Dimensions/Tolerances

width:	1000 mm ± 1.5 %
length:	± 1.5 %
thickness:	2, 3, 4, 5, 6mm ± 0.3 mm
density:	approx. 650 kg/m ³

→ color (G)

Product Data-Sheet

No. 9403 - R - 05

Edition: Oct 2009

5. Physical Characteristics

tensile strength:	approx. 0.5 N/mm ²	(EN ISO 1798)
elongation at break:	approx. 20%	(EN ISO 1798)
service temperature range:	- 30°C bis 80°C	
flammability rating:	B 2	(DIN 4102-1)
heat transmission coefficient:	0.04m ² K/W for 3mm slab	(DIN 52612)
impact sound improvement:	$\Delta L_w = 19$ dB without covering	(DIN EN ISO 140-8)
	$\Delta L_w = 24$ dB with textile floor	(DIN EN ISO 140-8)
	$\Delta L_w = 19$ dB with PVC-floor	(NF EN ISO 140-8)

6. Installation

Installation is to be carried out in accordance with the **DAMTEC® color** installation instructions.

Castor chair behaviour and residual indentation after static loading of the flooring can change in accordance with the insulating underlay used.

Only use underlay approved by the floor manufacturer.

Prior to any installation work, carefully read and observe the usage instructions and processing guidelines of the adhesive cement and floor finish manufacturers.

In case of doubt, please contact the manufacturer's applications engineering department for advice.

DISCLAIMER:

The information provided is intended only as a summary and general overview on matters of interest. The information is not intended to be comprehensive nor does it constitute expert advice. KRAIBURG RELASTEC shall not be liable for incidental and/or consequential damages directly or indirectly sustained, nor any loss caused by not complying with relevant industry/product standards and improper use of any Damtec® products. Due to varying construction methods, any other circumstances not stated above should be brought to the attention of KRAIBURG RELASTEC for review. For suitability to the prevailing site conditions, it is advised that certified testing should be conducted. It is recommended to seek further advice on your application with our technical staff prior to use.

The data sheet is not subject to any change service! All information is without guarantee.

Latest version of this document available on www.kraiburg-relastec.com/damtec