

→ **magic**

Product Data-Sheet

No. 9411 - R - 03

Edition: Oct 2009

1. Application Sector

DAMTEC® magic is a floor underlay for footfall sound reduction and thermal insulation; used in building construction and renovation, under parquet and laminate floors.

2. Material

Fine fibres of foamed rubber and PU foam with PU-elastomer bonding agent. Differences in coloration due to sunlight do not cause a loss of quality.

3. Appearance

colour: black and beige
surface: granular texture

4. Dimensions/Tolerances

width: 1,250 mm ± 1.5 %
length: ± 1.5 %
available thickness: 2, 3, 5 mm ± 0.3 mm
density: approx. 600 kg/m³

→ **magic**

Product Data-Sheet

No. 9411 - R - 03

Edition: Oct 2009

5. Physical Characteristics

| | | |
|----------------------------|---|----------------|
| tensile strength: | approx. 0.5 N/mm ² | (EN ISO 1798) |
| elongation at break: | approx. 40 % | (EN ISO 1798) |
| service temperature range: | - 30°C bis 80°C | |
| flammability rating: | B 2 | (DIN 4102-1) |
| impact sound improvement: | $\Delta L_w = 16$ dB with 7mm laminate (snap-fit connection) | (EN ISO 140-8) |

6. Installation

Installation is to be carried out in accordance with the *DAMTEC*® **magic** installation instructions.

Castor chair behaviour and residual indentation after static loading of the flooring can change in accordance with the insulating underlay used.

Only use underlay approved by the floor manufacturer.

Prior to any installation work, carefully read and observe the usage instructions and processing guidelines of the adhesive cement and floor finish manufacturers.

In case of doubt, please contact the manufacturer's applications engineering department for advice.

DISCLAIMER:

The information provided is intended only as a summary and general overview on matters of interest. The information is not intended to be comprehensive nor does it constitute expert advice. KRAIBURG RELASTEC shall not be liable for incidental and/or consequential damages directly or indirectly sustained, nor any loss caused by not complying with relevant industry/product standards and improper use of any Damtec® products. Due to varying construction methods, any other circumstances not stated above should be brought to the attention of KRAIBURG RELASTEC for review. For suitability to the prevailing site conditions, it is advised that certified testing should be conducted. It is recommended to seek further advice on your application with our technical staff prior to use.

The data sheet is not subject to any change service! All information is without guarantee.

Latest version of this document available on www.kraiburg-relastec.com/damtec

Page 2/2



Made in
Germany

